



- Material:**
- Waterproof Rate: IP67
 - LED Holder: PC+ABS, Black
 - LED: \varnothing 3mm, White
 - O-ring: EPDM, Black
 - Screw Nut: Nylon+GF
 - Operating voltage: 4V DC
 - Operating Temperature: -40°C~+80°C
 - For Panel Thickness 6.5mm Max.

Recommended Panel Cut-Out

(QC) Quality Control: Important Dimension to check

Unit: mm



| Scale | Free | | | | | Date | Name | Title |
|-----------|------|-----|--------------|------|------|--|----------|--------|
| TOLERANCE | | | | | | Drawn | 06.03.14 | Wilson |
| X. | ±0.3 | | | | | Approved | 06.03.14 | Groll |
| X.X | ±X | | | | | | | |
| X.XX | ±X | | | | | | | |
| DIM | TOL | | | | | | | |
| X.° | ±X° | | | | | | | |
| X.X° | ±X° | | | | | | | |
| Angle | TOL | Id. | Modification | Date | Name | 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us | | |

| | | | |
|-----------------|--|---|--|
| Title | | Waterproof LED | |
| | | White color, plastic, \varnothing 3.0mm | |
| ASSMANN WSW-No. | | A-LED8-1WAAS-PR7-1 | |
| Drawing-No. | | rev00 | |
| Replace | | Sheet 1/1 | |